

LUXURA X7 HYBRID

EQUIPMENT SPECIFICATIONS

Canopy Lamps:

Bench Lamps:

Facial:4 x 400Session Time:10 MinRoom AC Requirements:BTU 90Recommended Room Size:9 x 9 ftShipping Dimensions:91" x 4Shipping Weight:1100 lbDimensions:90.5"L

ProTech UV - 18 x 200W RenuvaTan Red Light - 6 x 200W Protech UV - 14 x 200W XL RenuvaTan Red Light 4 x 200W XL 4 x 400W 10 Minutes BTU 9000 A/C 9 x 9 ft 91" x 46" x 65" 1100 lbs 90.5"L x 53.5"W x 61.4"H

STANDARD FEATURES

LUXUIC

T-Max Integration w/ Quickstart Connection Touch Screen User Display Adjustable Body and Facial Cooling Ambient Flowlight Contoured Acrylic SoundAround Music System w/ Bluetooth Optional Upgrades: A/C Xsense Aromatherapy - 1 or 3 Scent Qsens Body Mister

ELECTRICAL REQUIREMENTS

Three Phase Connection

Electrical Rating:

Breaker Size: Buckbooster: 230V 3~32A 60 Hz; 3 Pole (3 Hots, 1 Ground) 40 Amp 2 * 1.0 Kva

Single Phase Connection

Electrical Rating: Breaker Size: Buckbooster:

230V ~50A 60 Hz; 2 Pole (2 Hots, 1 Ground) 60 Amp 1 * 1.5 Kva

Note: Equipment comes standard in three phase configuration. Buckboosters must be installed by licensed electrician in your state/county.

Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This produc should not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer."

*ProSun reserves the right to change design and specifications without notice.

• 510(K): K181455 •







2442 23rd Street North, St. Petersburg FL 33713